

KB-Zabbix-Server - Partition DB pleine

S'applique à : Zabbix, toutes versions.

Symptôme(s)

Impossible de lancer le service de base de donnée car la partition est pleine.

Problème

Par défaut, la DB garde en mémoire toutes les informations et par conséquent ne fait que grossir.

Solution

Exécuter un script de purge de la DB.

```
-- intervals in days
SET @history_interval = 7;
SET @trends_interval = 90;

DELETE FROM alerts WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@history_interval * 24 * 60 * 60);
DELETE FROM acknowledges WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@history_interval * 24 * 60 * 60);
DELETE FROM events WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@history_interval * 24 * 60 * 60);

DELETE FROM history WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@history_interval * 24 * 60 * 60);
DELETE FROM history_uint WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@history_interval * 24 * 60 * 60);
DELETE FROM history_str WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@history_interval * 24 * 60 *
```

```
60);  
DELETE FROM history_text WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@history_interval * 24 * 60  
* 60);  
DELETE FROM history_log WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@history_interval * 24 * 60 *  
60);  
  
DELETE FROM trends WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@trends_interval * 24 * 60 * 60);  
DELETE FROM trends_uint WHERE (UNIX_TIMESTAMP(NOW()) - clock) > (@trends_interval * 24 * 60 *  
60);
```

Sources

n/a

Revision #2

Created 2026-07-29 16:36:39 UTC by Olivier

Updated 2026-07-29 16:58:57 UTC by Olivier