

Bash - Build :

InstallPHPMyAdmin.sh

Status :

Terminé

Auteur :

Olivier

Dernière version :

V 1.0

Dernière modification :

03/03/2023

I. Fonctionnalités

Peut être utilisé dans les modes suivants : CLI

La commande "-help" est présente : non

II. Captures d'écran

n/a

III. Script

InstallPHPMyAdmin.sh

```
#!/bin/bash
```

```
#Take Arguments
```

```
PHPMYADMIN_DOWNLOAD_LINK="https://files.phpmyadmin.net/phpMyAdmin/5.2.0/phpMyAdmin-5.2.0-all-languages.zip"
```

```
BLOWFISH_SECRET=""
```

```
MYSQL_SERVER_ADDRESS="mysql"
```

```
#Upgrade system
```

```
apt update
```

```
apt upgrade -y
```

```
#Install Prerequisites
```

```
apt install -y vim wget zip
```

```
#disable interactive mode
```

```
export DEBIAN_FRONTEND=noninteractive
```

```
#Install apache+php
```

```
apt install -y apache2 php php-mysqli php-mbstring
```

```
#Clean install
```

```
apt autoclean
```

```
#Install PHP My Admin
```

```
cd /var/www/html
```

```
rm index.html
```

```
wget $PHPMYADMIN_DOWNLOAD_LINK
```

```
unzip phpMyAdmin-*
```

```
mv phpMyAdmin-*/.* ./
```

```
rm -rf phpMyAdmin-*
```

```
#Configure PHPMyAdmin
```

```
cp config.sample.inc.php config.inc.php
```

```
sed -i "s|cfg\[ 'blowfish_secret'\] = ''|cfg\[ 'blowfish_secret'\] = '$BLOWFISH_SECRET'|" /var/www/html/config.inc.php
```

```
/var/www/html/config.inc.php
```

```
sed -i "s|'localhost'|'$MYSQL_SERVER_ADDRESS'|" /var/www/html/config.inc.php
```

```
#create TMP directory and set rights on it
```

```
mkdir tmp
```

```
chown www-data:www-data tmp/
```

```
chmod 700 tmp/
```

```
#Restart apache2 service
```

```
service apache2 restart
```

IV. Changelog

V 1.0

- Installe apache2 et les modules php.
- Installe phpMyAdmin.
- Adapte les configurations.

Revision #1

Created 2026-07-17 14:50:46 UTC by Olivier

Updated 2026-07-17 14:50:46 UTC by Olivier